HI TOP TRACTOR

SHOGUN FV2446J

 SHIFTPILOT **MY21**





Power/Torque: 460ps/2,213Nm



Wheelbase: 3,910mm (J)



Suspension:

- Active Brake Assist 5 NEW
- **Electronic Stability Control**
- **Lane Departure Warning**

- **Adaptive Cruise Control**
- **Driver Fatigue Monitoring**
- Active Side Guard Assist NEW



SPECIFICATIONS - SHOGUN FV2446J 6x4

MODEL

WHEELBASE (mm)

GVM (kg)

GCM (kg)

ENGINE + TRANSMISSION

6x4 FV2446J HITOP

12 SP. SHIFTPILOT AIR SUSP.

FV74HJR4VFBB 3.910 (J)

Features

24,000

60,000

ENGINE	
Engine Version	FUSO OM470 6 Cyl. In-line DOHC
Displacement	11 Litre (10,671cc)
Power (DIN)*	460ps (338kW) @1600rpm
Torque (DIN)*	2,213Nm (1633lbft) @ 1100rpm
Air Cleaner	Vertical Intake Mounted on Clean Air Side (RH)
Emission Control	Selective Catalytic Reduction (SCR + DPF)
Emission Level	EURO 6 (ADR80/03)
*Gross Calculated	

TRANSMISSION CONTINUED

Standard + Power Modes: Calibrated for NZ Conditions Driver Activated Kick Down Skip Shift Function for Light Loads

RLow: 12.774


Crawler Mode
Rock-Free Mode
Eco Roll

Ratios 1st: 11.639 8th:2.050
2nd: 9.020 9th: 1.599
3rd: 7.035 10th: 1.239
4th: 5.452 11th: 1.000
5th: 4.400 12th:0.775
6th: 3.410 RHigh: 9.900

7th: 2.645

PTO Opening Rear

OM470 - T4



FRONT AXLE

Axle Version FUSO F900T "I" Beam

Max Operating Capacity (kg) 7,100 (Subject to suitable tyres + certification)

FRONT SUSPENSION

REAR SUSPENSION

Туре	Long Taper Leaf + Double Acting Shock Absorbers
Size (mm)	1,500 x 90

REAR AXLE

Details

Type

Park Brake

Engine Brake

Air Compressor

Air tanks

BRAKES

Size Front / Rear (mm)

Axle	D12 Hypoid Tandem Drive + Inter-Axle Diff Lock
Max Operating Capacity (kg)	21,600
Ratio	4.222:1

Trailing Arm + 2 Bag/Axle

Full Air Taper Roller Drum Brakes

 ${\sf Rear\ Wheels\ Spring\ Actuated}$

or remote control)

410x160/410x200

Height Control (adjustable from steering wheel

+Auto Adjust, EBS, ABS, ASR (Traction Control)

Jake Brake: Three-Stage including Shift Down Function – Max 335kW (460ps)

Two-Stage + ECU Control for Fuel Saving

FUEL

Injection System	X Pulse Common Rail High Pressure Direct Injection
Tank	400L Rectangular Alloy Tank + Locking Cap
AdBlue Exhaust Fluid	60L Tank + Locking Cap

Capacity

ELECTRICAL	
Voltage	24V Negative Ground, 100A Alternator
Battery Specification	Heavy Duty 2x12V, 150Ah / 20hr

CLUTCH

Type FUSO Single Plate Fully Automated

WHEELS AND TYRES

Wheels	10 x Alcoa Alloy 22.5x8.25" ISO 10 Stud
Tyre Size Front / Rear	275 / 70 R22.5

Alloy

TRANSMISSION Version FUSO SHIFTPILOT GENERATION 3 Automated Manual G330-12 Type / Speeds 12 Speed with Auto + Manual Modes Constant Mesh Non Synchromesh Transmission

SPECIFICATIONS - SHOGUN FV2446J 6x4

CHASSIS

Туре	Super Frame, Single Skin, Reinforced Parallel Channel
Size / Width (mm)	300x90x7.0/840

Refer to the bodybuilders guidelines on the Fuso website (www.fuso.co.nz) before mounting a body or modifying the chassis

INSTRUMENTS

monkomento.	
Gauges	Speedo / Tacho / Air pressure / Fuel level / Ad Blue level
Multi-Information Display accessed from steering wheel buttons	Digital Speedo Advanced Safety Systems Control Water Temperature Fuel Consumption Warning Lamps Service Indicators Hour Meter + Tripmeter Oil Level Check Alarm Clock
Steering wheel controls	Audio / Phone / Cruise Control / Multi-

STANDARD FEATURES

Cab Cooling and Heating	Climate Control Air Conditioning
Accessory Power	24V Accessory Power Outlet x 2
Driving	SMART Key Push Button Start + Keyless Central Locking Electric Windows Fluorescent Cabin Lamp Interior Reading Lamps Engine Idle Speed Control

CAB FEATURES

Туре	Hi Top All Steel 4 Point Air Suspended + Electric / Hydraulic Tilt Cab. Hi Top Model: 350mm More Headroom with Large Overhead Glovebox
Colour	Natural White (W31)
Seating Capacity	2 + Large Centre Console
Seat (driver)	Air Suspension Integrated Seat Belt Auto Levelling Height, Tilt, Lumbar + Dampening Adjust Armrest
Seats (passenger)	Bucket Seat with Integral Headrest
Interior	Fully Trimmed + Carpet on Floor Premium Rear Bunk Mattress + Reading Light Carpet on Floor + Curtains
External	Roof Mounting Points (max. static load 50kg) Front End-Outline Marker Lamps

SERVICE INTERVALS

60,000km full service / 15,000km safety inspection

60,000km full service intervals, depending on application/use. 15,000km safety inspection, with greasing, required for reliability and to maintain warranty cover.

WARRANTY

5 years / 500,000km

Simply have your vehicle serviced at an authorised FUSO Service Centre, at the recommended servicing intervals, and you are covered by an additional 2 year / 250,000km FUSO warranty on top of the first 3 years / 250,000km. That's a total of 5 years / 500,000km cover! Refer to the terms and conditions in the FUSO warranty booklet for full details.

SAFETY FEATURES

ACTIVE SAFETY FEATURES

Electronic Brake System (EBS)

Electronic Stability Control (ESC)	Yes
Active Brake Assist (ABA5)	Yes
Lane Departure Warning System (LDWS)	Yes
Active Attention Assist (Driver Fatigue Monitoring)	Yes
Proximity Control Assist (Adaptive Cruise Control)	Yes
Active Side Guard Assist (ASGA)	Yes

Steering Wheel

Rearview Mirrors

CAB: HI TOP	
Structure	ECE-R29 European Cab Strength (max front axle weight 6.5T) Door Side Impact Beams
Airbags	Driver (steering wheel)
Seatbelts	Pre-tensioner Integrated with seat (driver) Warning Light (driver)
Front Underrun Protector Beam (FUP)	Yes
LH Transom Window + Rear Quarter Glass	Yes

Yes

SAFETY

Leather, Tilt / Telescopic Adjustable

Remote Control, Heated + Separate

NEW

NEW

Convex Spotter (both sides) Auto-sensing Headlamps Auto High/Low Beam Activation Xtra Vision LED (low beam) Halogen (high beam)

	Manual height adjustment
Day Time Running Lights	Yes
Fog Lamps	Yes
Front Step Lights	Yes
Keyless Central Locking	Yes
Auto-sensing Wipers	Yes
Trailer Brake Control Lever	Yes

7" Touchscreen Media Unit AM/FM/DAB + USB + AUX Apple CarPlay + Android Auto Wi-Fi enabled for Internet Radio Bluetooth, 32GB capacity storage HD Reverse Camera included †

Yes (100km/h factory setting)
Yes

OPTIONS

† Additional Touchscreen Display Cameras (up to 4) / Truck Specific GPS Navigation / Reversing Sensors / Tyre Pressure Monitoring (up to 36 tyres)


KERB WEIGHTS AND MAX AXLE LOADS (kg) Vehicle Ratings** Max Axle Loadings** Kerb Weights* **GVM GCM** Front*** Rear 6x4 FV2446J Hi Top 12 Sp. SHIFTPILOT Air Susp. FV74HJR4VFBB 60,000 7,550 24.000 7.100 21.600 4.345 3.205 * Weights (est.) includes 10L fuel and are subject to 3.5% variation (+/-) ** Vehicle ratings and max axle loadings may be limited by local regulations. *** Subject to suitable tyres and certification

SPECIFICATIONS - SHOGUN FV2446J 6x4

PERFORMANCE	
Turning Circle (kerb to kerb - metres)	13.2
Electronically Speed limited to 100km/hr	Can be adjusted lower by dealer
Engine Speed (rpm) 90km/hr (top gear)	1,700
Gradeability at Rated GCM (theoretical)*	26%
*This is the section! = ==f================================	-l. Astualfarman

*This is theoretical performance only. Actual performance may vary under	
different conditions	

DIMENSIONS (mm)	
Wheelbase	3,910
Length Overall	6,740
Height Overall	3,650
Width Overall	2,490
Width Rear Axle	2,475
Width Front track	2,075
Width Rear Track	1,865
Width Frame	840
Height Frame at Rear Axle	990 (Air susp. inflated)



SHOGUN FV2446J 6x4 HI TOP - 'J' WHEELBASE

1000 UNIT: mm 20mm = 1m

Scale = 1:50 (20mm = 1 metre). This scale is accurate when used on the original spec sheet, be aware that enlarging these illustrations can alter the scale and cause incorrect measurements. Fuso New Zealand and its authorised dealers always recommend customers seek professional advice from independent sources before commencing any engineering activities.

A policy of continual improvement means that specifications detailed in this brochure are subject to change without notice. Contact your authorised Fuso dealer to confirm current specifications. Fuso is a registered trademark of Mitsubishi Fuso Truck & Bus Corporation. Copyright © Fuso NZ (2021)

