

CITY TIPPER

CANTER 616

DUONIC AMT OR MANUAL

ADVANCED
SAFETY
SYSTEMS



GVM:
5,995kg



Power / Torque:
110kW / 370Nm



Wheelbase:
2,500 mm (B)

- Electronic Brake System **NEW**
- Electronic Stability Control **NEW**
- Active Emergency Braking System **NEW**
- Lane Departure Warning System **NEW**
- 3yr/100,000km warranty
- 30,000km service intervals

SPECIFICATIONS - 616 CITY TIPPER

MODEL

4x2 616	CITY TIPPER	6 SP.	AMT	FEA61BR3SFBC(T)
4x2 616	CITY TIPPER	5 SP.	MAN	FEA61BR4SFBC(T)

WHEELBASE (mm)

2,500 (B)
2,500 (B)

GVM (kg)

5,995
5,995


GCM (kg)

9,500
9,500

ENGINE

Engine Version	FUSO 4P10-T4 Diesel
Configuration	4 Cyl. In-line DOHC, 4-Valve
Type	Variable Geometry Turbo Charged Air to Air Intercooled
Displacement	3 litre (2998cc)
Power (DIN)	110kW @ 2840~3500rpm
Torque (DIN)	370Nm @ 1350~2840rpm
Maximum Engine Speed (rpm)	4100
Compression Ratio	17.5:1
Cooling System/Oil Cooler	Water cooled, 13.0L capacity. Engine oil cooler
Air Cleaner	Paper Element Type with Restrictor Indicator. Vertical Intake Mounted on Clean Air Side (RH)
Cold Start Preheat	Standard
Emission Control	Diesel Particulate Filter (DPF) Exhaust Dash Display DPF Status 0~9 (Empty~Full) Parked Regeneration possible from 7~9
Emission Level	EURO 5 (ADR 80/03) and EEV rated (Enhanced Environmentally-Friendly Vehicle)

4P10-T4



FUEL

Injection System	Bosch Common Rail Direct Injection Bosch Piezo Technology Injectors
Tank Type	Rectangular Steel Tank with Locking Cap
Fuel Capacity (L)	70
Filtration	Filter with Water Separator and Indicator Sensor

ELECTRICAL

Voltage	12V Negative Earth
Alternator Capacity	12V-110 amp
Battery Specification	Heavy Duty 115D31L x 2
Headlamp Type	Halogen 2 x 55W/60W
Fog lamp in bumper	Standard

CLUTCH

	DUONIC AMT	Manual
Clutch Model	DUONIC Automated Manual (no clutch pedal)	FUSO C4W30
Type	Dual Clutch (Wet Multi-plate)	Single Dry Plate, Direct Hydraulic Type, 300mm

TRANSMISSION

	DUONIC AMT	Manual
Version	FUSO DUONIC M038S6	FUSO M038S5
Type/Speeds	6 Speed Automated Manual with Auto and Manual Modes	5 Speed with In-Dash Gearshift Lever
Features	Virtually Instant Gear Changes Synchromesh 2nd-5th In-Dash Gear Lever with Park Brake Position ECO Mode to Minimise Fuel Usage	
Ratios	1st: 5.397 2nd: 3.788 3rd: 2.310 4th: 1.474	5th: 1.000 6th: 0.701 Rev. 5.397
PTO Opening	LH Side Direct with pump	LH Side Direct with pump

FRONT AXLE

Axle	FUSO F200T "I" beam
Design Capacity (kg)	2,600
Max Operating Capacity (kg)	2,570

FRONT SUSPENSION

Type	Multi Leaf with Stabiliser Bar and Double Acting Shock Absorbers
Size (mm)	1,150 x 70

REAR AXLE

Axle	FUSO D033 Full Floating Banjo Type with Positive Locking Limited Slip Differential (LSD).
Ratio	5.285:1
Design Capacity (kg)	4,500
Max Operating Capacity (kg)	4,500

REAR SUSPENSION

Type	Steel Suspension
Details	Multi Leaf with Stabiliser Bar and Double Acting Shock Absorbers
Size Main Leaves (mm)	1,100 x 70

STEERING

Power Assisted	Tilt/Telescopic Adjustable Steering Wheel
----------------	---

BRAKES

Type	Hydraulic Dual Circuit with Front and Rear Twin Caliper Discs
Size Front/Rear (mm)	293 x 40
Features	ABS + EBD + EBS Exhaust Brake Brake Priority System
Park Brake	Transmission Mounted

SPECIFICATIONS - 616 CITY TIPPER

ADVANCED
SAFETY
SYSTEMS

WHEELS AND TYRES

Wheel Size	16.0 x 5.5K-115
Tyre Size Front/Rear	205/85R16 / 205/85R16 Traction
Spare Tyre Carrier	Yes

CHASSIS

Size (mm)	190 x 60 x 5
-----------	--------------

Refer to the bodybuilders guidelines on the Fuso website (www.fuso.co.nz) before mounting a body or modifying the chassis

INSTRUMENTS

Gauges	Speedometer with Odometer Tachometer Fuel Level Water Temperature
Colour Information Display	Fuel Consumption DPF Bar Chart from 1~9 Water Temperature Maintenance Reminder System Date and Time Tripmeters

STANDARD FEATURES

Cab Cooling and Heating	Air Conditioner/Heater/Demister
Accessory Power	12V Accessory Power Outlet/Cigar Lighter
Driving	Keyless Central Locking Electric Windows
Radio	AM/FM + CD + USB + Bluetooth
Storage	Dual Overhead Storage Pockets In-Dash Centre Document Storage Door Storage Pockets Lockable Glove Box

CAB FEATURES

Type	All Steel Forward Control Manual Tilt
Mounting	Hydroelastic 4 Point
Colour	Natural White (W31)
Interior	Fully Trimmed cab with vinyl floor covering
Seating Capacity	3
Seat (driver)	Heavy Duty with LH Arm Rest Adjustable Lumbar Support
Seats (passenger)	Flat Folding 2 Passenger Bench

SERVICE INTERVALS

30,000km full service / 15,000km safety inspection

30,000km full service intervals, depending on application/use.
15,000km safety inspection, with greasing, required to maintain warranty cover and ensure optimum performance.

WARRANTY

3 years / 100,000km

All tipper and body equipment covered by 12mth/unlimited km warranty.
Refer to terms and conditions in the FUSO warranty booklet for full details.

SAFETY FEATURES

ACTIVE SAFETY FEATURES

Electronic Brake System (EBS)	Yes	NEW
Electronic Stability Control (ESC)	Yes	NEW
Active Emergency Braking System (AEBS)	Yes	NEW
Lane Departure Warning System (LDWS)	Yes	NEW

CAB

Structure	ECE R-29 Reinforced Cab Side Intrusion Bar
Airbags	Driver's (steering wheel) Passenger's (dashboard) NEW
Seatbelts	ELR 3-Point (+ height-adjustable with pre tensioner for driver) Lap Belt (centre passenger)
Steering Wheel	Energy-absorbing Adjustable (height and reach)
Rearview Mirrors	Heated
Fog Lamps	Yes
Keyless Central Locking	Yes

CHASSIS

Speed Limiter	Yes (activated and adjustable by FUSO dealer)
Anti-Lock Braking System (ABS)	Yes
Anti-Slip Regulator (ASR)	Yes
Electronic Brake Force Distribution (EBD)	Yes
Disc Brakes	Auto-Adjusting, 4 Wheel Dual Caliper
Brake Priority System	Yes
Exhaust Brake	Yes
Hill Start Assist	Yes (adjustable engagement on manual transmission)
Reverse Warning Buzzer	Yes
Anti Roll Bar	Yes
Brake Wear Indicator	Yes

OPTIONS

7" Touchscreen Media Unit	AM/FM/DAB + USB + AUX Apple CarPlay and Android Auto Wi-Fi enabled for Internet Radio Bluetooth 32GB capacity storage HD Reverse Camera included †
---------------------------	---

† Up to 4 additional Display Cameras

Truck Specific GPS Navigation

Reversing Sensors

Tyre Pressure Monitoring System

Wireless Phone Charge Pocket

Extended Warranty Additional 2yrs / 100,000km

KERB WEIGHTS AND MAX AXLE LOADS (kg)

Model		Vehicle Ratings**		Max Axle Loadings**		Kerb Weights*		
		GVM	GCM	Front	Rear	Front	Rear	Total
4x2 616 City Cab Tipper 6 Sp. AMT	FEA61BR3SFBC(T)	5,995	9,500	2,570	4,500	1,480	1,170	2,650
4x2 616 City Cab Tipper 5 Sp. MAN	FEA61BR4SFBC(T)	5,995	9,500	2,570	4,500	1,465	1,165	2,630

* Weights (est.) includes 10L fuel and spare wheel and are subject to 2.5% variation (+/-)

** Vehicle ratings and max axle loadings may be limited by local regulations.

SPECIFICATIONS - 616 CITY TIPPER

PERFORMANCE

	DUONIC	Manual
Turning Circle (kerb to kerb - metres)	10.2	10.2
Road Speed (km/h) at Max Engine Speed	120	120
Engine Speed (rpm) at 90km/hr (top gear)	2395	2280
Gradeability at Rated GVM (theoretical)*	51%	50%


Notes *This is theoretical performance only. Actual performance may vary under different conditions

DIMENSIONS (mm)

Wheelbase	2,500
Length Overall	4,690
Height Overall	2,125
Width Overall	1,880
Width Rear Axle	1,880
Width Front Track	1,390
Width Rear Track	1,235
Width Frame	700

REAR BODY

Type:	ShinMayawa Tipper Body
Body Capacity (m ³):	2.0
Inside Body Dimensions (mm):	
Length x Width x Height	3,050 x 1780 x 370
Floor Height From Ground to Rear Deck Floor	965
Thickness : Floor	3.2
Front and Side Panel	2.3
Tail Panel	3.2
Sides and Tailgate Operation	Drop sides with two-way tailgate hinging at the top & bottom
Tipping Mechanism:	Under body-hydraulic cylinder with link mechanism
Tipping Performance: Tip Angle (deg)	55
Lifting Time (sec)	20
Lowering Time (sec)	20



CANTER 616 CITY TIPPER - 'B' WHEELBASE

Scale = 1:50 (20mm = 1 metre). This scale is accurate when used on the original spec sheet, be aware that enlarging these illustrations can alter the scale and cause incorrect measurements. Fuso New Zealand and its authorised dealers always recommend customers seek professional advice from independent sources before commencing any engineering activities.

A policy of continual improvement means that specifications detailed in this brochure are subject to change without notice. Contact your authorised Fuso dealer to confirm current specifications. Fuso is a registered trademark of Mitsubishi Fuso Truck & Bus Corporation. Copyright © Fuso NZ (2021)